Surge protection made easy – SPD selection aid

according to the current IEC 60364-4-44 and IEC 60364-5-53



T3

1 Installation location: Main distributor at the infeed point of the system

with a spacing to the main distributor > 10 m

3 Installation location: Terminal as close as possible to the resource to be protected

Residential buildings. multiple-occupancy dwellings, etc.



Without external lightning protection system with earth cable infeed (IEC 60364-5-53 and 60364-4-44)

TT/TN-S MCF30-NAR-TT Item no. 5096 961

MCF25-NAR-TNC

Item no. 5096 950

Item no. 5096 953

MCF50-NAR-TT

Item no. 5096 975

MCF50-NAR-TT+FS

Item no. 5096 977

Item no. 5096 971

TN-C MCF38-NAR-TNC

MCF25-NAR-TNC+FS

MCF30-NAR-TT+FS Item no. 5096 963 TN-C

Pre-meter area

Also usable in buildings with exposed cable

infeed

T1 T2

T1 T2

TN/TT V20-3+NPE-280 Item no. 5095 253

Meter area

V20-3+NPE-280+FS Item no. 5095 333

T2

TN/TT V20-3+NPE-280 Item no. 5095 253

V20-3+NPE-280+FS Item no. 5095333



T2 T3

T2

Alternatively

V10 COMPACT 255



V10 COMPACT-FS



V10 COMPACT-AS Item no. 5093 391



Universal fine protection FC-D Item no. 5092 80 0



3-way socket with audible error signalling CNS-3-D Item no. 5092 70 1

Surge protection module 45

With optical function display



Buildings of lightning protection classes III and IV (e.g. housing and commercial and office buildings)



Exposed cable supply (according to IEC 60364-5-53 and 60364-4-44)



(recommendation)

MCF38-NAR-TNC+FS Item no. 5096 973



V50-3+NPE-280 Item no. 5093 526

TN/TT

V50-3+NPE-280+FS Item no. 5093 533



T1 T2

Hat rail device with visual



Device with acoustic

Item no. 5092 45 1

Item no. 5092 46 0

signalling

ÜSM-A

with acoustic signalling



ÜSS 45-0

Item no. 6117473

Device for installation behind sockets through simple attachment







Buildings of lightning protection classes I to IV (e.g. industrial buildings, computer centres or hospitals)



MCF100-NAR-TT+FS Item no. 5096 988

TN-C

Item no. 5096 982

MCF75-NAR-TNC+FS Item no. 5096 983



TN-S/TT MCF100-3+NPE+FS Item no. 5096 987

TN-C/IT

Also usable in the pre-meter areas

T1 T2

MCF75-3+FS Item no. 5096 981

Protection device for 2 phases

ÜSM-A2

ÜSM-10-230I2P+PE Item no. 5092 42 6









Earthed antenna structures



TT/TN-S

MCF100-NAR-TT Item no. 5096 985

MCF75-NAR-TNC



Surge protection made easy – SPD selection aid

according to the current IEC 60364-4-44 and IEC 60364-5-53



